



TP7F54M
 TP7F54M(H) **108-cell**
 395 - 415W
 10BB Half-cut Mono Perc



SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems



PERFORMANCE WARRANTY

12 Years
 Quality Assurance

2 Years
 Power Output Guarantee

Linear Performance Warranty

KEY FEATURES



10BB Half-cut Cell Technology
 New circuit design, lower internal current, lower Rs loss
 Ga doped wafer, attenuation < 2% (1st year) / 0.55% (Linear)



2% more power generation, lower LCOE



2 times of industry standard Anti-PID test



IP68 Waterproof Level

ELECTRICAL CHARACTERISTICS

Testing Condition	STC	NMOT	STC	NMOT	STC	STC
Maximum Power (Pmax/W)	395	294	400	298	405	395
Operating Voltage (Vmpp/V)	30.85	28.8	31.05	29.0	31.24	29.2
Operating Current (Impp/A)	12.81	10.23	12.89	10.30	12.97	10.36
Open-Circuit Voltage (Voc/V)	36.75	34.6	37.00	34.8	37.25	35.1
Short-Circuit Current (Isc/A)	13.69	11.04	13.78	11.11	13.86	11.17
Module Efficiency (%)	20.20		20.50		20.70	

STC: Irradiance 1000W/m², Spectra at AM1.5, Module Temperature 25 °C. Power output tolerance: 0~+5W, Temperature tolerance: ±2°C
 NMOT : Irradiance 800W/m², Spectra at AM1.5, Ambient Temperature 20 °C, Wind speed 1m/s

MECHANICAL CHARACTERISTICS

Cell Type	Monocrystalline Silicon (10Busbar)
No. of Cells	108pcs in series (6*18)
Module Dimensions	1722*1134*30mm (67.80*44.65*1.18inches)
Weight	21.5kg (47.4lbs.)
Front Glass	3.2mm AR Coating Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68, 3 Bypass Diodes
Output Cables	4mm ² (IEC), 12AWG(UL) 350mm(+),250mm(-) or Customized Length
Connectors	T01/LJQ-3-CSY/MC4/MC4-EV02

APPLICATION CONDITIONS

Maximum System Voltage	1000V/1500V/DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse	25A
Safety Protection Class	Class


TEMPERATURE CHARACTERISTICS

Temperature Coefficient of Pmax	-0.35%/°C
Temperature Coefficient of Voc	-0.26%/°C
Temperature Coefficient of Isc	+0.048%/°C
Nominal Module Operating Temperature(NMOT)	43±2°C

PACKING CONFIGURATION

Pieces Per Pallet	36	36(USA)
Pieces Per Container(40'HQ)	936	828

I-V CURVE



TECHNICAL DRAWINGS



The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Suzhou Talesun Solar Technologies Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.