



TP7F60M
TP7F60M(H) **120-cell**

440 - 460W

10BB Half-cut Mono Perc



KEY FEATURES

SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems



PERFORMANCE WARRANTY

12 Years
Quality
Assurance

25 Years
Power Output
Guarantee

Linear Performance Warranty

www.talesun.com

marketing.hq@talesun.com

ELECTRICAL CHARACTERISTICS

: C. :
C

MECHANICAL CHARACTERISTICS

	Monocrystalline Silicon (10Busbar)
	120pcs in series (6*20)
	1908*1134*35mm (75.12*44.65*1.38inches)
	24.3kg (53.6lbs.)
	Anodized Aluminium Alloy
	IP68, 3 Bypass Diodes
	4mm² (IEC), 12AWG(UL) 300mm in Length or Customized Length
	T01/LJQ-3-CSY/MC4/MC4-EV02

I-V CURVE

APPLICATION CONDITIONS

	1000V/1500V/DC
	-40°C~+85°C
	25A
	Class II

TECHNICAL DRAWINGS

TEMPERATURE CHARACTERISTICS

PACKING CONFIGURATION



The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Suzhou Talesun Solar Technologies Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recenys.